according to UK REACH Regulation

Diotrol Dio-Shield Wood ETC Harz

Revision date: 13.05.2025 Product code: 60150 Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Diotrol Dio-Shield Wood ETC Harz

UFI: SGUQ-5Q68-710P-16UF

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Matter 2K-Lack zum Schutz gegen Verunreinigungen. Schlussanstrich im DioShield Wood-System

1.3. Details of the supplier of the safety data sheet

Company name: Diotrol AG

Street: Bodenackerstrasse 64
Place: CH-4657 Dulliken
Telephone: +41 622853070
E-mail: info@diotrol.com
Internet: www.diotrol.com

Responsible Department: Technik **1.4. Emergency telephone** 145

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Skin Sens. 1; H317 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Bis (1,2,2,6,6-pentamethyl-4-piperidinyl)sebacate

Signal word: Warning

Pictograms:



Hazard statements

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P273 Avoid release to the environment.

P280 Wear protective gloves and eye protection/face protection.

P261 Avoid breathing Dampf / Aerosol.
P333 If skin irritation or rash occurs:
P313 Get medical advice/attention.

P501 Dispose of contents/container to industrieller Verbrennungsanlage.

2.3. Other hazards

No information available.

according to UK REACH Regulation

Diotrol Dio-Shield Wood ETC Harz

Revision date: 13.05.2025 Product code: 60150 Page 2 of 9

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification (GB CLP Regulation)				
5131-66-8	3-butoxypropan-2-ol; propylene glycol monobutyl ether				
	225-878-4	603-052-00-8			
	Skin Irrit. 2, Eye Irrit. 2; H315 H319				
107-98-2	1-methoxy-2-propanol; monopropyl	ene glycol methyl ether		1 - < 5 %	
	203-539-1	603-064-00-3			
	Flam. Liq. 3, STOT SE 3; H226 H336				
41556-26-7	Bis (1,2,2,6,6-pentamethyl-4-piperidinyl)sebacate				
	255-437-1				
	Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H317 H400 H410				
82919-37-7	methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate				
	280-060-4				
	Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H317 H400 H410				

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
107-98-2	203-539-1	1-methoxy-2-propanol; monopropylene glycol methyl ether	1 - < 5 %
	dermal: LD50 = 11000 mg/kg; oral: LD50 = > 5000 mg/kg		

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Medical treatment necessary.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

After ingestion

Rinse mouth immediately and drink 1 glass of of water.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

according to UK REACH Regulation

Diotrol Dio-Shield Wood ETC Harz

Revision date: 13.05.2025 Product code: 60150 Page 3 of 9

Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

5.2. Special hazards arising from the substance or mixture

Non-flammable. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Use personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

No special measures are necessary.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

Advice on general occupational hygiene

Take off contaminated clothing. Wash hands before breaks and after work. When using do not eat, drink, smoke, sniff.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed.

Hints on joint storage

Von stark sauren und alkalischen Materialien sowie Oxidationsmitteln fernhalten.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
107-98-2	1-Methoxypropan-2-ol	100	375		TWA (8 h)	WEL
		150	560		STEL (15 min)	WEL

according to UK REACH Regulation

Diotrol Dio-Shield Wood ETC Harz

Revision date: 13.05.2025 Product code: 60150 Page 4 of 9

8.2. Exposure controls



Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye protection/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Use of protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Flüssig
Colour: weiss
Odour: Arttypisch

Melting point/freezing point: 0 °C
Boiling point or initial boiling point and 100 °C

boiling range:

Flammability: not determined Lower explosion limits: 0.9 vol. % Upper explosion limits: 13.1 vol. % Flash point: 63 °C 260 °C Auto-ignition temperature: Decomposition temperature: not determined pH-Value (at 20 °C): 7-9 Viscosity / kinematic: 75 mm²/s

(at 20 °C)

Water solubility: easily soluble

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined Vapour pressure: 13.3 hPa

(at 20 °C)

Density (at 20 °C): 1.055 g/cm³
Relative vapour density: not determined
Particle characteristics: not applicable

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

The product is not: Explosive.

according to UK REACH Regulation

Diotrol Dio-Shield Wood ETC Harz

Revision date: 13.05.2025 Product code: 60150 Page 5 of 9

Oxidizing properties

The product is not: oxidising.

Other safety characteristics

Solvent content: 9%

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

none

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
107-98-2	1-methoxy-2-propanol; m	1-methoxy-2-propanol; monopropylene glycol methyl ether			
	oral	LD50 > 5000 mg/kg	Rat	IUCLID	
	dermal	LD50 11000 mg/kg	Rabbit		

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

May cause an allergic skin reaction. (Bis (1,2,2,6,6-pentamethyl-4-piperidinyl)sebacate; methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate)

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

according to UK REACH Regulation

Diotrol Dio-Shield Wood ETC Harz

Revision date: 13.05.2025 Product code: 60150 Page 6 of 9

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether					
	Acute fish toxicity	LC50 4600 - 10000 mg/l	96 h	Leuciscus idus	IUCLID	
	Acute algae toxicity	ErC50 > 1000 mg/l		Selenastrum capricornutum		
	Acute crustacea toxicity	EC50 > 500 mg/l	48 h	Daphnia magna	IUCLID	

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether	-0,437

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

according to UK REACH Regulation

Diotrol Dio-Shield Wood ETC Harz

Revision date: 13.05.2025 Product code: 60150 Page 7 of 9

No dangerous good in sense of this transport regulation. 14.1. UN number or ID number: No dangerous good in sense of this transport regulation. 14.2. UN proper shipping name: 14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation. 14.4. Packing group: No dangerous good in sense of this transport regulation.

14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

14.7. Maritime transport in bulk according to IMO instruments

No dangerous good in sense of this transport regulation.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

9 % (94.95 g/l)

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2010/75/EU on industrial 9 % (94.95 g/l)

emissions:

Directive 2004/42/EC on VOC in

paints and varnishes:

Information according to Directive

2012/18/EU (SEVESO III):

Not subject to 2012/18/EU (SEVESO III)

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

according to UK REACH Regulation

Diotrol Dio-Shield Wood ETC Harz

Revision date: 13.05.2025 Product code: 60150 Page 8 of 9

Abbreviations and acronyms

Flam. Liq: Flammable liquids Skin Irrit: Skin irritation Eye Irrit: Eye irritation Skin Sens: Skin sensitisation

STOT SE: Specific target organ toxicity - single exposure

Aquatic Acute: Acute aquatic hazard Aquatic Chronic: Chronic aquatic hazard CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

EC/EEC: European Community/European Economic Community

EU: European Union

CAS: Chemical Abstracts Service DNEL: Derived No Effect Level DMFI: Derived Minimal Effect Level PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate LC50: Lethal concentration, 50%

LD50: Lethal dose, 50% LL50: Lethal loading, 50% EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic vPvB: verv persistent, verv bioaccumulative

M-factor: Multiplying factor

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Regulations concerning the international carriage of dangerous goods by rail MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container VOC: volatile organic compound SVHC: Substance of Very High Concern

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety

assessment, chapter R.20 (Table of terms and abbreviations).

Classification for mixtures and used evaluation method according to GB CLP Regulation

May cause an allergic skin reaction.

Classification	Classification procedure
Skin Sens. 1; H317	
Aquatic Chronic 3; H412	Calculation method

Rele

ic Chronic 3; H412	Calculation method
levant H and EUH stater	nents (number and full text)
H226 F	lammable liquid and vapour.
H315 C	Causes skin irritation.

May cause drowsiness or dizziness. H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

Causes serious eye irritation.

Further Information

H317

H319

H336

The information is based on the present level of our knowledge. It does not, however, give assurance of

according to UK REACH Regulation

Diotrol Dio-Shield Wood ETC Harz

Revision date: 13.05.2025 Product code: 60150 Page 9 of 9

product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)