



# Diotrol Golden Oil ML – Maintenance Lotion

#### #70250

#### **Description**

Diotrol Golden Oil ML – Maintenance Lotion is a water-based, organic wood care lotion for worn-out or faded wooden surfaces which had been treated with Diotrol Golden Oil. For this product only renewable raw materials are used. This oil-in-water emulsion is free from any biocidal active ingredients, contains 0% VOC and no metal-based drying agent. It is produced with no petrochemical ingredients.

The use of Diotrol Golden Oil ML - Maintenance Lotion depends on how intensive the surface has been used. It is therefore recommended to use a periodic application to obtain the surface quality.

Δ	nn	lic	ati/	n	are	3

To refresh wooden surface like floor or furniture and all kinds of woodwork.

### Binder & reactive agents

Natural oils from regenerating raw materials, beeswax, carnauba wax

#### **Appearance**

Whitish, milky

Smell

Swiss stone pine (natural essence)

**Flashpoint** 

Not applicable

**Spec. Gravity** 

1.0 kg/l

**Packaging** 

50ml, 250ml, 1L, 5L

Storage

12 months in appropriate, cool place in closed original packaging. Store in a cool and dry place.

#### **Procedure**

#### **Precondition**

Stir well before use. Substrate must be free from dust.

#### **Procedure**

1. Clean the substrate with Diotrol Golden Oil Preparator or Diotrol Golden Oil Floorsoap.





- 2. Spread the lotion with a cloth, sponge, or brush evenly on the surface. Only apply it in thin layers.
- 3. Rub dry with a dry cloth or mechanically with white pad. If needed, polish the surface with a dry polishing cloth.

#### Consumption

#### Approximately 0.5L/100m<sup>2</sup>

May depend on the nature and absorbency of the substrate.

Apply only little lotion, this avoids a sticky surface or wrinkles. Do not leave wet spots.

#### **Dilution**

Ready for use.

## Drying at 18 – 20°C (at 50% rel. moisture)

After dry polishing, the surface can be walked on again. Do not immediately expose the surface to liquids.

#### **Cleaning of tools**

Immediately after use, while still wet, clean with warm water. Dried remains and rags can only be washed out in solvents.

#### Safety advice

Please read safety data sheet.

#### Remarks

This information is due to the current, technical know-how and is meant as recommendation and advice. Concerning all mentioned paint coat structures, we do not maintain completeness. Insufficient wood quality, lack of constructive wood-protection, drying cracks in solid wood and otherwise identified faults have to be admonished by the customer before painting or glazing. Because of the diversification and different kinds of substrates and practice, the user has to test our products mainly for his own purpose and has to use and apply them properly. For this, he is fully responsible. Verbal advice must be fixed obligatory by a signed document. If a new issue will be current, this edition will be no more available.

May 2022, sky