

Diotrol Golden Oil Care

Maintenance Oil

#70270

Description Diotrol Golden Oil Care – Maintenance Oil is an organic, natural Maintenance oil. This special product is used to refurbish worn out and fading wooden surfaces which are oiled with Diotrol Golden Oil. The usage is depending on how heavily the surface has been used. We recommend a regular usage to maintain the quality of the surface.

Diotrol Golden Oil Care is produced by using natural oils from regenerating raw materials and pure wax from carnauba. It is free of cobalt drying agents, contains 0% VOC and no harmful substances.

Application area For refurbishing wooden surfaces such as floors, furniture, and all types of wooden objects.

Binder & reactive agents Natural oils from regenerating raw materials and carnauba wax

Active agents / Biocide Free of active substances, contains no biocide

Looks Light honey

Smell Typical (vegetable oils)

Flashpoint >120°C

Spec. Gravity 0.938 kg/l

Packaging 1L, 5L, 25L, 200L

Storage 12 months in appropriate, cool place in closed original packaging. Close packaging properly after usage. Prevent from freezing.

Oxygen and the high content of oils can lead to skin formation in open or brittle containers. This must be carefully removed before use.

Procedure **Requirements**
Stir well before use. The surface must be dust-free.

Procedure

1. Prepare the surface with Diotrol Golden Oil Preparator or Diotrol Golden Oil Floorsoap.
2. Spread the oil evenly with a cloth, sponge, or brush.
3. Rub dry with a dry cloth or machine with a white pad. The coating result depends on the wood's condition. In case of unknown wood quality, a small test-coating is advisable.

Consumption

Approximately 0.5L/100m²

May depend on the nature and absorbency of the substrate.

Apply only little lotion, this avoids a sticky surface or wrinkles. Do not leave wet spots.

Dilution

Ready for use.

Drying at 18 – 20°C (at 50% rel. moisture)

- dust-dry and stackable after polishing
- dried thoroughly after 3 to 4 days
- usable after 5 to 7 days

Depending on the temperature, the application quantity, the air humidity, and the substrate's absorbency.

Cleaning of tools

Immediately after use with turpentine substitute or universal thinner.

Important remarks

- Saturated rags can ignite by themselves. Spread and let them dry in the open air, or store them in an airtight metal can.
- Keep away from sources of ignition. Avoid sources of fire during work.
- Keep away from food for humans and animals.

Safety advice

Please read safety data sheet.

Remarks

This information is due to the current, technical know-how and is meant as recommendation and advice. Concerning all mentioned paint coat structures, we do not maintain completeness. Insufficient wood quality, lack of constructive wood-protection, drying cracks in solid wood and otherwise identified faults have to be admonished by the customer before painting or glazing. Because of the diversification and different kinds of substrates and practice, the user has to test our products mainly for his own purpose and has to use and apply them properly. For this, he is fully responsible. Verbal advice must be fixed obligatory by a signed document. If a new issue will be current, this edition will be no more available.

May 2022, sky