

Diotrol Golden Oil Allclean

Concentrate

#70350

Description

Diotrol Golden Oil Allclean is a biological universal cleaner, which removes grease professionally and removes dirt hygienically. The water-based all-rounder removes highly effective fat, soot, nicotine deposits and other pollution.

Diotrol Golden Oil Allclean can also be used as a cleaner in vehicles and machinery, as well as in high-pressure cleaners and floor brush machines with a suction system, and also in food processing plants.

Diotrol Golden Oil Allclean has proven itself especially for cleaning wooden facades. It acts highly effective as algae remover, and sustainable as mould remover.

Diotrol Golden Oil Allclean is a concentrate and must be diluted with water before use.

Application

- Dilute Diotrol Golden Oil Allclean with water in a mixing ratio of 1:10 to 1:100, depending on the degree of soiling.
- Spray the mixture on or apply it with a brush, sponge or Scotch-Brite pad and leave it to take effect for 5–10 minutes. Make sure that the mixture does not dry out (avoid direct sunlight).
- For persistent dirt, clean the surface thoroughly with a brush or sponge.
- Rinse well with water.
- For smooth surfaces, rub the area with a dry cloth if necessary.

Surface-specific dilution recommendations

Wood / oil-based paints

- Mild cleaning (surface dirt removal): work with a dilution of 1:40.
- Strong cleaning (oil-dissolving): work with a dilution of 1:10.

Aluminium / non-ferrous metals

- Only work with a dilution of 1:40.

- ***We generally recommend carrying out a test on a concealed area beforehand when working on sensitive surfaces.***

Binder & reactive agents

Water, sodium hydroxide, ionic and anionic surfactants, glycols

Environmental benefits

Fast and complete biodegradability (OECD 301F). Leaves no traces of hazardous substances in the household or in the environment. Not harmful to waters.

Appearance	Colorless
Packaging	1L
Storage	12 months in appropriate, cool place in closed original packaging. Store in a cool and dry place.
Safety advice	Please read safety data sheet.
Remarks	<p>This information is due to the current, technical know-how and is meant as recommendation and advice. Concerning all mentioned paint coat structures, we do not maintain completeness. Insufficient wood quality, lack of constructive wood-protection, drying cracks in solid wood and otherwise identified faults have to be admonished by the customer before painting or glazing. Because of the diversification and different kinds of substrates and practice, the user has to test our products mainly for his own purpose and has to use and apply them properly. For this, he is fully responsible. Verbal advice must be fixed obligatory by a signed document. If a new issue will be current, this edition will be no more available.</p>

July 2025, sky