

Diotrol Entgrauer

Diotrol Degreyer

#82500

Description Diotrol Degreyer agent returns the natural look to wood and restores all greyed kind of wood. It does refresh wood that was exposed to UV radiance and weathering. Diotrol Degreyer agent refreshes greyed shutter, planking and massive furniture.

Application area greyed wood outdoors like terraces, window shutters

Binder & reactive agents Hydrous dilution of organic acids, completely biodegradable.

Active agents / Biocide None

Spec. Gravity Approx. 1.000 kg/l

Appearance Colorless

Packaging 1L, 2L, 5L

Storage If stored properly in cool place, Diotrol Degreyer can be stored for 12 months in closed original packaging. Close opened containers tightly.
Avoid contact with oxidizing metals. Protect from frost, and from excessive heat (>30°C).

Surface Mechanically remove moss, lichen as well as dried discharge of natural resin prior to use. Heavily soiled parts must be previously cleaned with Diotrol Allclean.

Processing tools Paint brush, paint roller (long hair)

Instruction Stir well before use. Do not dilute. The jellylike product is ready to use.

- Moisture surface before use. This enhances the effect of Diotrol Degreyer.
- Apply Diotrol Degreyer generously with a brush or paint roller (long hair).
- Treat vertical parts from top to bottom.
- Allow Diotrol Entgrauer to react for 10 to 15 minutes maximum. Where necessary, work over with a nylon brush (caution, corrosive splashes)

- Rinse the surface with plenty of water. If high-pressure cleaners are used, reduce the pressure as not to agitate the wood fibres.
- On heavily soiled surfaces, the cleaning process may have to be repeated.
- Let dry well.

Advice Make a cleaning attempt beforehand in a place that is not visible.
Drying of Diotrol Degreyer must be avoided.

Consumption You can clean a surface between 2 and 5 square metres of surface with one litre.
Depends on the nature and absorbency of the surface and degree of soiling.

Temperature Do not use Diotrol Degreyer when temperature is below +5°C or above +30°C.

Dilution Ready for use.

Drying at 18 – 20°C (at 50% rel. moisture) After washing Diotrol Degreyer off, allow the surface to dry for 2 to 3 days. Drying depends on the weather and varies on the water absorption and texture of the wood.

Cleaning of tools Immediately after use with water.

Safety advice Please read safety data sheet.
Do not allow to get into the soil. Collect scraped off residues (with a plastic cover) and dispose properly.

Remarks This information is due to the current, technical know-how and is meant as recommendation and advice. Concerning all mentioned paint coat structures, we do not maintain completeness. Insufficient wood quality, lack of constructive wood-protection, drying cracks in solid wood and otherwise identified faults have to be admonished by the customer before painting or glazing. Because of the diversification and different kinds of substrates and practice, the user has to test our products mainly for his own purpose and has to use and apply them properly. For this, he is fully responsible. Verbal advice must be fixed obligatory by a signed document. If a new issue will be current, this edition will be no more available

January 2023, sky