

Diotrol Aqua Wallcare

#80700

Description Diotrol Aqua Wallcare is a waterbased one-coat system for new and light coniferous wood walls indoor. A combination of antioxidants and radical scavenger protect light coniferous wood from darkening. A lighting effect without bleaching materials or pigments supports the long-life lasting photo stabilizing effect. Areas which are covered by pictures or decorative material do not sign up or show any shades. Soiling may be cleaned with mild soap water.

Application area Suited for all kind of woodwork indoors which are made from raw new and light coniferous wood.

Binder / reactive agents Pre-cross-linked natural oils of regenerating natural resources and photo stabilizing additives.

Active agents / Biocide none

Solids Appr. 40 %

Spec. Gravity 1.00 kg/l

Gloss Silky flat

Tints Colorless to milky bleaching shade

Packaging 1L, 5L, 20L

Storage 12 months in appropriate, cool atmosphere and closed original packing. Close packing properly after use.

Prevent from freezing. Once open, packing must be closed properly.

Surface The surface must be clean, free from grease and wax. It must be free from any paint or other coatings. May not have more than 9 - 13% moisture.

In order to assess the product practical, we recommend to apply a sample at a non-visible area.

Processing Brushing, rolling, applicator or spraying

Consumption 80 – 110 g/m² per coating. Depends on the condition of the substrate.

Dilution	Ready to use, if necessary dilute with water.
-----------------	---

Paint system	Diotrol Aqua Wallcare must be applied directly in one layer on raw an untreated coniferous wood. The protecting effect becomes activated by direct contact to wood substance. It does not lighten wood which is already darkened. <i>For further advice, please contact technical service.</i>
---------------------	--

Drying at 18 – 20°C (at 75% rel. moisture)	The protecting effect is achieved after 24 h. The coating is washable. Use mild cleaning agents. The coating is not wet rub resistant.
---	---

Cleaning of tools	Immediately after use, clean with water. Dried material must be cleaned with brush cleaner or washing solvent.
--------------------------	--

Safety advice	Please read safety data sheet.
----------------------	--------------------------------

Remarks	This information is due to the current, technical know-how and are meant as recommendation and advice. Concerning all mentioned paint coat structures, we do not maintain completeness. Insufficient wood quality, lack of constructive wood-protection, drying cracks in solid wood and otherwise identified faults have to be admonished by the customer before painting or glazing. Because of the diversification and different kinds of substrates and practice, the user has to test our products mainly for his own purpose and has to use and apply them properly. For this, he is fully responsible. Verbal advice must be fixed obligatory by a signed document. If a new issue will be current, this edition will be no more available
----------------	---

Oktober 2018, mt/ms