

Diotrol Aqua Allclean

Concentrate

#82510

Description Diotrol Aqua Allclean is a biological universal cleaner, which removes grease professionally and removes dirt hygienically. The water-based all-rounder removes highly effective fat, soot, nicotine deposits and other pollution.

Diotrol Aqua Allclean can also be used as a cleaner in vehicles and machinery, as well as in high-pressure cleaners and floor brush machines with a suction system, and also in food processing plants.

Diotrol Aqua Allclean has proven itself especially for cleaning wooden facades. It acts highly effective as algae remover, and sustainable as mould remover.

Diotrol Aqua Allclean is a concentrate and must be diluted with water before use.

-
- Application**
- Add 100 - 400 g Diotrol Aqua Allclean per litre of water. Depending on the degree of soiling.
 - Spray or apply Diotrol Aqua Allclean on the surface, leave it on for at least 5 minutes.
 - If there's heavy soiling use a brush or sponge to clean the surface thoroughly
 - Rinse well with water.
 - If necessary, polish smooth surfaces with a dry cloth.
 - To clean aluminium or non-ferrous metals dilute Diotrol Aqua Allclean in a mixing ratio of 1:40.
 - For sensitive surfaces always carry out a preliminary test on a non-visible place.

Binder & reactive agents Water, sodium hydroxide, ionic and anionic surfactants, glycols

Environmental benefits Fast and complete biodegradability (OECD 301F). Leaves no traces of hazardous substances in the household or in the environment. Not harmful to waters.

Appearance Colorless

Packaging 1L

Storage 12 months in appropriate, cool place in closed original packaging. Store in a cool and dry place.

Safety advice Please read safety data sheet.

Remarks This information is due to the current, technical know-how and is meant as recommendation and advice. Concerning all mentioned paint coat structures, we do not maintain completeness.

Insufficient wood quality, lack of constructive wood-protection, drying cracks in solid wood and otherwise identified faults have to be admonished by the customer before painting or glazing. Because of the diversification and different kinds of substrates and practice, the user has to test our products mainly for his own purpose and has to use and apply them properly. For this, he is fully responsible. Verbal advice must be fixed obligatory by a signed document. If a new issue will be current, this edition will be no more available.

December 2022, sky