

Diotrol Golden Oil WPC-Oil

#70230

Description

Diotrol Golden Oil WPC-Oil is an organic, natural maintenance oil for surfaces made of WPC, Resysta, bamboo, and domestic or tropical wood. This special product is used to refurbish worn out and fading WPC and wooden surfaces. The usage is depending on how heavily the surface has been used. We recommend a regular usage to maintain the quality of the surface. Diotrol Golden Oil WPC-Oil is extremely economical and easy to apply.

Diotrol Golden Oil Care is produced by using natural oils from regenerating raw materials and pure wax from carnauba. It is free of cobalt drying agents, contains 0% VOC and no harmful substances.

Application area

For refurbishing surfaces made of WPC, Resysta, bamboo. Can also be used on domestic and tropical wood.

Ideally suited for terraces, garden furniture, screens, fences, etc.

Binder & reactive agents

Natural oils from regenerating raw materials and carnauba wax

Active agents / Biocide

Free of active substances, contains no biocide

Looks

Light honey

Smell

Typical (vegetable oils)

Flashpoint

>120°C

Spec. Gravity

0.938 kg/l

Packaging

500ml, 1L, 5L

Storage

12 months in appropriate, cool place in closed original packaging. Close packaging properly after usage. Prevent from freezing.

Oxygen and the high content of oils can lead to skin formation in open or brittle containers. This must be carefully removed before use.

Procedure

Requirements

Stir well before use. The surface must be dust-free.

Procedure

1. Clean soiled surfaces with *Diotrol Golden Oil Allclean*.
 - 1.1. If there are still grey areas after cleaning, these can be treated with *Diotrol Golden Oil Degreaser*.
2. After the surfaces is completely dry, spread the oil evenly with a cloth, sponge, or brush.
3. Rub dry with a dry cloth or machine with a white pad. The coating result depends on the wood's condition. In case of unknown wood quality, a small test-coating is advisable.

Do not apply when the outside temperature is below 10°C or above 30°C or when the humidity is more than 70%. Avoid direct sunlight.

We recommend applying Diotrol Golden Oil WPC-Oil during announced, longer periods of good weather (5-7 days).

Consumption

Approximately 0.5L/100m²

May depend on the nature and absorbency of the substrate.

Apply only little oil, this avoids a sticky surface or wrinkles. Do not leave wet spots.

Dilution

Ready for use.

Drying at 18 – 20°C (at 50% rel. moisture)

- dust-dry and stackable after polishing
- dried thoroughly after 3 to 4 days
- usable after 5 to 7 days

Depending on weather condition and exposure to daylight.

Cleaning of tools

Immediately after use with turpentine substitute or universal thinner.

Important remarks

- Saturated rags can ignite by themselves. Spread and let them dry in the open air, or store them in an airtight metal can.
- Keep away from sources of ignition. Avoid sources of fire during work.
- Keep away from food for humans and animals.

Safety advice

Please read safety data sheet.

Remarks

This information is due to the current, technical know-how and is meant as recommendation and advice. Concerning all mentioned paint coat structures, we do not maintain completeness. Insufficient wood quality, lack of constructive wood-protection, drying cracks in solid wood and otherwise identified faults have to be admonished by the customer before painting or glazing. Because of the diversification and different kinds of substrates and practice, the user has to test our products mainly for his own purpose and has to use and apply them properly. For this, he is fully responsible. Verbal advice must be fixed obligatory by a signed document. If a new issue will be current, this edition will be no more available.

