

Diotrol Aqua Woodprimer

#80380 - 82

Description Diotrol Aqua Woodprimer serves as a base for light glaze build-ups on dark woods. The opaque wood primer with open-pored character penetrates deeply and ensures an ideal anchorage of the subsequent glazes. Dark wood does not need to be sanded or stained.

Diotrol Aqua Woodprimer is a water-based natural oil mixture and can be painted over with all Diotrol Aqua products. This opaque primer forms a high UV protection and considerably increases the life of light glaze build-ups due to the pigment content.

Application area Primer for lightening and levelling dark woods for a light glaze build-up.
Do not use on surfaces that can be walked on!

Binder / reactive agents Mixture of natural oils

Active agents / Biocide None

Solids Approx. 63 %

Spec. Gravity 1.180 kg/l

Gloss Mat

Tints WP-32 Corn
WP-33 Caramel
WP-34 Salmon

Packaging 1L, 5L

Storage Can be stored for at least 12 months in well-sealed original containers. Store in a cool and dry place. Protect from frost and do not expose to temperatures > 30°C.

Avoid contact with oxidisable materials. Skin formation may occur in opened containers due to the high oil content.

Surface

- The wood must be clean, free of grease, resin and wax and must not have more than 9 - 13% moisture.

The coating result depends on the wood's condition. In case of unknown wood quality, a small test-coating is advisable.

Processing Brushing or rolling

Consumption 80 - 100 g / m²
May vary depending on the condition and absorbency of the substrate.

Dilution ready to use. If needed dilute with 10 – 30% water.

Paint system 1 x Diotrol Aqua Woodprimer, Corn, Caramel or Salmon, depending on the final shade.

Retouch any dark areas that still show through so that there is an even surface.

2x Diotrol Aqua Natural Oil Glaze, tinted.

Drying at 18 – 20°C (at 50% rel. moisture)

- Dust dry after 2-3 hours
- Touch resistant after 6 hours
- Can be painted over after 24 hours

Indoors: Allow to dry in daylight and ventilate well.

Exterior: Avoid direct sunlight. Do not apply at temperatures below +5°C.

Cleaning of tools Clean with water immediately after use.
Dissolve dry paint residues with nitro thinner or brush cleaner.

Safety advice Please read safety data sheet.

Remarks This information is due to the current, technical know-how and are meant as recommendation and advice. Concerning all mentioned paint coat structures we do not maintain completeness. Insufficient wood quality, lack of constructive wood-protection, drying cracks in solid wood and otherwise identified faults have to be admonished by the customer before painting or glazing. Because of the diversification and different kinds of substrates and practice, the user has to test our products mainly for his own purpose and has to use and apply them properly. For this, he is fully responsible. Verbal advice must be

fixed obligatory by a signed document. If a new issue will be current, this edition will be no more available

May 2020, B, mt